



### Sail numbers

Sails shall be made and measured according to Section G of the ISAF Equipment Rules 1997-2000 except where varied herein.

#### 16 SAILS:

Sails shall be made and measured according to Section G of the ISAF Equipment Rules 1997-2000 except where varied herein.

As an alteration to RRS Appendix H1.3(a) the following items shall be displayed on each side of the mainsail:

- (a) **420 emblem** below and adjacent to the top batten.
- (b) **National letters** above and/or below, adjacent to the second batten from the top, port and starboard not overlapping each other.
- (c) **Sail Numbers** above and below, adjacent to the third batten and above an imaginary line projecting at right angles to the luff from a point one-quarter ( $\frac{1}{4}$ ) of the distance measured from the tack, to the head of the sail (see mainsail diagram).

National letter(s) shall not be in line with the sail number.

The emblem shall be blue and not less than 480mm high.

Numbers and letters shall be red and of the following minimum dimensions:

Height 300mm

Width 200mm (except number 1 and letter I)

Thickness 45mm

Minimum space between adjoining figures 60mm.

The colour of numbers on the spinnaker is optional but it shall contrast with the colour of the panel to which they are fixed, and of the same colour, full painted and on both sides.

National letters are optional on both sides of the spinnaker.

*To paint the sailnumber on the spinnaker we suggest to put the spinnaker on the mainsail, to trace the outlines with a pen and than to fill the numbers with a large felt-tip marker.*